

TECHNICAL FEATURES

FEATURE	TECHNICAL FEATURES	STANDARD	ESTABLISHED LIMITS	HARDSCAPE 3CM
REGULARITY	RECTANGULARITY	ISO 10545-2	± 0.6 %	COMPLYING
	STRAIGHTNESS OF SIDES	ISO 10545-2	± 0.5 %	COMPLYING
	LENGHT AND WIDTH	ISO 10545-2	± 0.6 %	COMPLYING
	SURFACE FLATNESS	ISO 10545-2	± 0.5 %	COMPLYING
	THICKNESS	ISO 10545-2	± 0.5 %	COMPLYING
STRUCTURAL	CLASSIFICATION	EN1339	VALUE DECLARED	U30
	MODULUS OF RUPTURE	ISO 10545-4	≥ 35 N/mm ²	51,1 N/mm ²
	WATER ABSORPTION	ISO 10545-3	≤ 0,5 %	COMPLYING
	BREAKING STRENGHT	ISO 10545-4	≥ 1300 N	29672 N
CHEMICAL	CONTENT OF LEAD AND CADMIUM	ISO 10545-15	VALUE DECLARED	ABSENT
THERMAL HYGROMETRIC	FROST RESISTANCE	ISO 10545-12	TEST PASSED	GUARANTEED
SAFETY	SKID RESISTANCE	DIN 51130	VALUE DECLARED	R11
		DIN 51097		A+B*

PACKING LIST

24"x24"

Product	3cm
size (inch)	24x24
thickness (inch)	1 1/8
sqft/plt	176
sqft/box	8
sqft/pc	4
boxes/plt	22
pc/plt	44
pc/box	2
pallet (inch)	26x50
lb/plt	2348
lb/box	105
lb/pc	53

16"x32"

Product	3cm
size (inch)	16x32
thickness (inch)	1 1/8
sqft/plt	192
sqft/box	7.11
sqft/pc	3.56
boxes/plt	27
pc/plt	54
pc/box	2
pallet (inch)	34x50
lb/plt	2558
lb/box	93
lb/pc	47

8"x32"

Product	3cm
size (inch)	8x32
thickness (inch)	1 1/8
sqft/plt	192
sqft/box	7.11
sqft/pc	1.78
boxes/plt	27
pc/plt	108
pc/box	4
lb/plt	2558
lb/box	93
lb/pc	23